











# Portable Evaporative Cooler







## Automatic pump shut-off

When a customer forgets to fill the tank it won't come back from rental with burned-out parts



Easy water fill
Fill 10-gal tank from manual door for 3 to 4 hours of runtime or leave connected for continuous fill




### Adjusts to space

Lockable wheels and lightweight design provide ultimate portability while louvers can adjust airflow left-to-right

- ✓ Quiet operation at less than 60 dB
- ✓ Safe GFCI connection with low amp draw suitable for most available circuits
- ✓ Durable UV protected case

Coverage	950 sq. ft.
Water Tank Capacity	10.3 gallons
Run time per tank	3-4 hours
Unit Dimensions	38" x 24" x 17"
Unit Weight	45 lbs

### Cooling Technology



Water from an onboard tank is pumped to the top of a filter-like cooling pad. Then, a 3100 CFM fan pulls warm, environmental air over the filter and pushes out air with a cooling effect 30+ feet.

Cooling Chart		Relative humidity						
		20%	30%	40%	50%	60%	70%	
	75°F	-24	-21	-18	-12	-14	-12	)
	80°F	-24	-22	-19	-17	-15	-13	F away)
<b>₽</b>	85°F	-26	-23	-20	-18	-15	-13	a≷
윤	90°F	-27	-24	-21	-18	-16	-13	r°
ē	95°F	-28	-25	-22	-19	-16		ole . 10
Ambient Temp	100°F	-30	-26	-23	-19	-17		Š.
ğ	105°F	-31	-27	-24	-20	-17		pro
Αď	110°F	-33	-28	-24	-21			Feels (appr
	115°F	-34	-29	-25	-21			

### WORLD PROVIDER OF INNOVATIVE CLIMATE SOLUTIONS