

AT150RS

AQUATRAP® LGR DEHUMIDIFIER

The Most Competitively Priced LGR in its Category

Stackable. Efficient. Affordable.

The AT150RS portable LGR dehumidifier from Abatement Technologies® is designed to make your structural drying work faster and your bottom line healthier.

FEATURES & BENEFITS

- Units may be stacked up to two high for space saving storage
- Folding handle is easily moved out of the way
- “No tools” filter changes
- Discharge hose equipped with quick connects on both ends
- Control panel is recessed for protection
- Handles are located on front and above wheels for easy lifting
- Soft-start compressor cycle reduces startup load
- Meets CSA/UL standards

TECHNICAL SPECIFICATIONS

DESCRIPTION	AT150RS
Water Removal (90° F/90% RH)	140 Pints/66L per day
Water Removal @ AHAM (80° F/60% RH)	85 Pints/40L per day
Operating temperature range.	34° - 100° F
Refrigerant	R410A
Max Power Consumption	1090 Watt
Voltage/Cycle	115V/60Hz
Amperage	7.0A max
Rated Air Flow	354CFM/600m3/h
Control Panel	Touchpad
Defrost Type	Sensor controlled thermodynamic defrost
Air Filter	Pleated Filter (P/N: AT250FLTR)
Water Pump	Centrifugal
Housing	Rotomolded plastic
Drain Hose Length	32'/10m
Cord Length	9.84'/3m
Dimensions (LxWxH)	19.6" x 19.6" x 33.5" (500mm x 500mm x 850mm)
Weight	87lb/39.5kg

Specifications subject to change without prior notice.



THE AT150RS IS BEST SUITED FOR:



DISASTER RESTORATION



ABATEMENT & REMEDIATION



HEALTH CARE CONSTRUCTION



HEALTH CARE FACILITIES

ABATEMENT
TECHNOLOGIES®
LEADERS IN CLEAN AIR

CA: 1 800 827 6443

ABATEMENT.CA

IAQINFO@ABATEMENT.CA

US: 1 800 634 9091

ABATEMENT.COM

IAQINFO@ABATEMENT.COM