

## ■ Specifications

Model		KC70	KC120HC		
Machine weight	lbs. (kg)	992 (450)	1951 (885)		
Max. loading capacity	lbs. (kg)	1543 (700)	2646 (1200)		
Engine	Model	Kubota OC60	Kubota Z482		
	Type	Oil and air-cooled, 4 cycle, diesel	Liquid-cooled, 4 cycle, vertical diesel		
	No. of cylinder	1	2		
	Output	HP (kW) / rpm	6.0 (4.5) / 1700	12.7 (9.5) / 3600	
	Starting system	Electric	Electric		
Dimensions	Length	in. (mm)	95.1 (2415)	103.9 (2640)	
	Width	in. (mm)	34.6 (880)	37.4 (950)	
	Height	in. (mm)	51.6 (1310)	79.3 (2015) / 60.8 (1545)	
	Min. ground clearance	in. (mm)	5.1 (130)	5.7 (145)	
	Track center-to-center distance	in. (mm)	24.4 (620)	28.3 (720)	
	Bed	Length	in. (mm)	49.2 (1250)	57.9 (1470)
		Width	in. (mm)	32.3 (820)	33.7 (855)
		Height	in. (mm)	13.8 (350)	12.6 (320)
Capacity (Struck/Heaped)		cu. yd. (m <sup>3</sup> )	0.42 (0.32) / 0.52 (0.40)	0.52 (0.40) / 0.68 (0.52)	
Undercarriage	Track width	in. (mm)	7.9 (200)	9.1 (230)	
	Ground contact length	in. (mm)	38.6 (980)	46.5 (1180)	
No. of shift change	Forward / Reverse	3 / 3	2 / 2		
Traveling speed	1st	mph (km/h)	0-1.0 (0-1.6) / 0-0.9 (0-1.5)	0-2.4 (0-3.8) / 0-1.3 (0-2.1)	
Forward/	2nd	mph (km/h)	0-1.9 (0-3.1) / 0-1.9 (0-3.0)	0-4.3 (0-6.9) / 0-2.4 (0-3.9)	
Reverse	3rd	mph (km/h)	0-3.1 (0-5.0) / 0-3.0 (0-4.8)	-	
Dumping type		Hydraulic	Hydraulic		
Dumping direction		Front	Front,Sides		
Dumping angle	deg.	Approx. 68	Front 56,Sides 61		
Brake type		Internal expanding type	Wet multi-plate type		



### KUBOTA CANADA LTD.

Head Office: 5900 14th Avenue, Markham, Ontario L3S 4K4 TEL:(905)294-7477 FAX:(905)294-6651  
 Delta Distribution Centre: 7979 82nd Street, Delta, B.C. V4G 1L7 TEL:(604)940-8061 FAX:(604)940-8067  
 Drummondville Distribution Office: 5705 Place Kubota, Drummondville, PQ, J2B 6V4 TEL:(819)478-7151 FAX:(819)478-7836

Visit our web site at: [www.kubota.ca](http://www.kubota.ca)



Printed in Japan Cat. No. 8757-01-CL  
 0807.Q.SP.HW.a.50