

# KX033-4 OPTIONS

## STANDARD EQUIPMENT

### Safety system

- Engine start safety system
- Travel motor with disc brake
- Swivel motor with disc brake
- All hydraulic control

### Working equipment

- Auxiliary hydraulic circuit 1 with proportional control on right control lever
- 2 working lights on cab and 1 light on the boom
- Dozer blade with float function
- Thumb bracket and relief valve

### Operator's Space

- ROPS/OPG (TOP Guard, Level I) canopy
- Weight-adjustable full suspension seat
- Retractable seat belt
- Hydraulic pilot control levers with wrist rests
- Travel levers with foot pedals
- Two pattern selection system
- Digital panel with diagnosis function
- 12V power source
- Cup holder
- Horn

### Engine/Fuel system

- Double element air filter
- Auto idling system
- Water separator with drain cock

### Undercarriage

- 11.8" (300mm) rubber track
- 1 × upper track roller
- 5 double-flange track rollers on each side
- 2-speed travel switch on dozer lever
- 2-speed travel with auto-shift

### Hydraulic system

- Pressure accumulator
- Hydraulic pressure checking ports
- Straight travel circuit
- Third line hydraulic return
- 2 variable pumps and 1 gear pump
- Adjustable maximum oil flow on auxiliary hydraulic circuits 1
- Auxiliary switch (AUX1) on right control lever

### Others


- Tool box
- Grease gun holder

## OPTIONAL EQUIPMENT

- Cab with A/C
- Canopy lights
- Rear working lights
- Beacon lights
- Angle blade with float function and BOE
- Travel alarm
- Spark arrest muffler

## WORKING RANGE

Model				KX033-4
A	Max. digging height	ft. in. (mm)		16'4" (4980)
B	Max. dumping height	ft. in. (mm)		11'7" (3530)
C	Max. digging depth	ft. in. (mm)		10'6" (3210)
D	Max. vertical digging depth	ft. in. (mm)		7'4" (2235)
E	Max. digging radius at ground	ft. in. (mm)		16'10" (5120)
F	Max. digging radius	ft. in. (mm)		17'2" (5230)
G	Min. turning radius	W/o swing	ft. in. (mm)	6'7" (2020)
		W swing	ft. in. (mm)	4'11" (1510)
H	Min. tail turning radius	ft. in. (mm)		4'1" (1250)




## LIFTING CAPACITY

Canopy rubber

LIFT POINT HEIGHT (ft)		LIFTING CAPACITY OVER-FRONT BLADE DOWN unit=1000 lbs			LIFTING CAPACITY OVER-SIDE unit=1000 lbs		
		LIFT POINT RADIUS (ft)			LIFT POINT RADIUS (ft)		
		10	14	MAX	10	14	MAX
GL	6	1.37	1.23	1.23	1.37	0.89	0.84
	4	1.66	1.29	1.27	1.42	0.87	0.81
	2	1.92	1.36	1.30	1.38	0.86	0.81
	0	2.10	1.38	1.34	1.35	0.86	0.83



Machine with ROPS canopy and rubber crawler, without bucket



# SPECIFICATIONS

Model				KX033-4	KX033-4 Angle Blade
Type of ROPS / OPG (TOP Guard, Level I)				Canopy / Cab	
Type of tracks				Rubber / Steel	
Engine	Model			Kubota D1703M-DI-E4	
	Output (SAE J1995 gross)		HP (kW) / rpm	24.8 (18.5) / 2200	
	Output (SAE J1349 net)		HP (kW) / rpm	23.2 (17.3) / 2200	
	Displacement		cu. in. (cc)	100.5 (1647)	
Dimensions	Overall length		ft. in. (mm)	15'6" (4730)	
	Overall height		ft. in. (mm)	8'1" (2480) / 8'1" (2470)	
	Overall width		ft. in. (mm)	5'1" (1550)	
	Min. ground clearance		in. (mm)	11.4 (290)	
	Boom offset	Right / Left	ft. in. (mm)	1'4.1" (410) / 1'5.7" (450)	
	Blade lift	Upper / Low	ft. in. (mm)	1'2.4" (365) / 1'2.8" (375)	
Hydraulic system	Pump capacity		GPM (ℓ/min)	10.5 (39.6) x 2 / 5.5 (20.9) x 1	
	Auxiliary hydraulic flow		GPM (ℓ/min)	15.8 (60)	
	Max. breakout force	Bucket / Arm	lbs. (kgf)	8138 (3694) / 3867 (1756)	
Drive system	Travel speed		Low / High mph (km/h)	1.9 (3.0) / 2.9 (4.6)	
	Max. traction force		Low speed lbs. (kgf)	6091 (2763)	
	Tumbler distance		ft. in. (mm)	5'5.6" (1665)	
	Crawler length		ft. in. (mm)	6'10.6" (2100)	
	Shoe width	Rubber / Steel	in. (mm)	11.8 (300)	
	Ground contact pressure	Canopy Rubber / Steel	psi (kgf/cm <sup>2</sup> )	4.365 (0.307) / 4.482 (0.315)	4.583 (0.322) / 4.700 (0.331)
		Cab Rubber / Steel	psi (kgf/cm <sup>2</sup> )	4.559 (0.321) / 4.676 (0.329)	4.776 (0.336) / 4.894 (0.344)
Swing system	Unit swing speed		rpm	8.9	
	Boom swing angle	Left / Right	degree	70 / 48	
Blade	Dimensions	Width	ft. in. (mm)	5'1" (1550)	
		Height	ft. in. (mm)	1'1.5" (345)	1'3.2" (385)
	Max. lift above ground		in. (mm)	14.4 (365)	15.9 (405)
	Max. drop below ground		in. (mm)	14.8 (375)	18.9 (480)
	Angle	Left / Right	degree	-	25 / 25
Hydraulic oil (Reservoir / System)			gal (ℓ)	11.8 (44.6) / 16.1 (61)	
Fuel reservoir			gal (ℓ)	12.4 (46.9)	
Operating weight (Including operator's weight @ 175 lbs.)	Canopy	Rubber / Steel	lbs. (kgf)	7420 (3365) / 7616 (3454)	7781 (3529) / 7978 (3618)
	Cab	Rubber / Steel	lbs. (kgf)	7742 (3511) / 7938 (3600)	8104 (3675) / 8300 (3764)

# DIMENSIONS



Unit: ft. in. (mm)

Kubota Canada Ltd. reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for Canada only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

©2016 Kubota Corporation



## KUBOTA CANADA LTD.

Head Office:  
5900 14th Avenue, Markham, Ontario L3S 4K4  
TEL: (905) 294-7477

Visit our web site at: [www.kubota.ca](http://www.kubota.ca)

